






The ancient precious stone, Onyx, has been an unfailingly coveted material since antiquity. Used as early as the Egyptian Second Dynasty in carvings and ornaments, the gemstone is characterized by bands of white and gold veining woven into a smooth, almost translucent appearing body. Onyx has endured the ages, much like porcelain tile and will transform your floor into a work of art, stunning everyone who has the pleasure of walking upon it. The depth of movement in the collection creates a richer and more profound profile, allowing designers to add texture, dimension and a robust sensation to their spaces. Offered in a rectified, polished or matte body, with five designer colors and a variety of mosaic and trim pieces, you can truly get creative and draw inspiration from both historic and contemporary dwellings with this fresh tile.







ONYX / WHITE






24"x48" / WHITE polished
















12 **ONYX**



3"x6" Brick Mosaic polished / IVORY .12"x24" / IVORY polished . 24"x24" / IVORY matte





3"x6" Brick Mosaic polished / IVORY .12"x24" / IVORY polished . 24"x24" / IVORY matte

î

1415

15

17


16 **ONYX**




12"x12" Mosaic polished . 24"x48" / IVORY polished . 24"x24" / LIGHT GREY polished










ONYX / BEIGE

20 **ONYX**

















ONYX / LIGHT GREY





12"x12" Mosaic polished / IVORY .12"x24" / LIGHT GREY matte







12"x12" Mosaic polished / IVORY .12"x24" / LIGHT GREY matte

u.

28







ONYX / DARK GREY

32 ONYX



3"x6" Brick Mosaic polished / WHITE .12"x24" / DARK GREY matte










SIZES & SHADE VARIATION

sizes:



Colors shown may vary from actual product. Final selection should be made from actual product samples.

mosaics & trim pieces:

12"x12"

Mosaic Matte (36 dot) 2"x2"

_			

1101720 White 1101721 Ivory 1101722 Beige 1101723 Light Grey 1101724 Dark Grey

12"x12"

Brick Mosaic Matte 3"x6"



1101725 White 1101726 Ivory 1101727 Beige 1101728 Light Grey 1101729 Dark Grey

3"x24" Bullnose matte

1101715 White 1101716 Ivory 1101717 Beige 1101718 Light Grey 1101719 Dark Grey 12"x12" Mosaic Polished (36 dot) 2"x2"

1	1()1	7	7	0	White
					-	
1	1(רנ	1	1	T.	lvory
4.	1 (٦ı	7	7	S	Beige
	I C	וו	1	1	_	Deige

1101773 Light Grey


1101774 Dark Grey 12"x12" Brick Mosaic Polished 3"x6"



3"x24" Bullnose Polished



1101765 White 1101766 Ivory 1101767 Beige 1101768 Light Grey 1101769 Dark Grey







Technical Specifications

This product meets or exceeds all standards described in ANSI A137.1 & A137.3. Este product cumple o exceed todos los estandares de ANSI A137.1 & A137.3.

	SPECS		INDUSTRY STANDARD	MILE®stone VALUES	
	WATER ABSORPTION	ASTM C373	≤0.5%	≤0.5%	
*	SURFACE WEAR RESISTANCE	ANSI A137.1	Surface Wear-resistance properties of glazed vitreous and porcelain tiles.	ALL RESIDENTIAL / COMMERCIAL	
~	CHEMICAL RESISTANCE	ASTM C650	A tile sample is placed in continuous contact with a variety of chemicals for 24 hours. Sample must show no visible defects.	NOT AFFECTED	
*		ANSI	INDOOR ≥0.42 WET	≥0.42 WET	
	D.C.O.F. AcuTest®	A326.3	OUTDOOR >0.55 WET	>0.55 WET 2	CM & GRIP
×	STAIN RESISTANCE	ASTM C1378	Surfaces are exposed to staining agents for 24 hours followed by four cleaning procedures. Results are recorded post cleaning.	NOT AFFECTED	
	BREAKING STRENGTH GAUGED PORCELAIN	ASTM C1505	≥175 lbf	≥200	lbf
ڡ۫	BREAKING STRENGTH	ASTM C648	≥275 lbf	≥300 lbf ≥2500 lbf	
	BREAKING STRENGTH OUTDOOR 2CM	ASTM 1505	2000 lbf (10.9 kN)		
**	RESISTANCE TO FREEZE	ASTM C1026	A tile sample is subjected to repeated processes of freezing and thawing. Sample must show no visible defects.	RESISTANT	
	WARPAGE EDGE	ASTM C485	±0.40% or ±0.05 in (±1.8 mm)	± 0.40%	Rectified
	WARPAGE DIAGONAL	ASTM C485	±0.40% or ±0.07 in (±1.8 mm)	± 0.40%	Rectified
H	WEDGING	ASTM C502	±0.25% or ±0.03 in (±0.8 mm)	± 0.25%	Rectified
	WARPAGE EDGE	ASTM C485	±0.50% or ±0.07 in (±1.8 mm)	± 0.50%	Calibrated
	WARPAGE DIAGONAL	ASTM C485	±0.50% or ±0.07 in (±1.8 mm)	± 0.50%	Calibrated
H	WEDGING	ASTM C502	±0.50% or ±0.08 in (±2.0 mm)	± 0.50%	Calibrated
ı	THICKNESS	ASTM C499	Range: ± 0.04 in	≤0.04 in	

• Due to the inherent nature of fired porcelain tile, it is important to note that the coefficent of friction may vary within and between product runs.

Cleaning & Maintenance / Routine Care Instructions



Scan the QR code with your smartphone.

Green Memberships & Accreditations

DESCRIPTION

Recycled Constitute	Defines post-consumer content of as much as 3% recycled glass which reduces landfill impact.
Recurrence Control	Defines pre-consumer content of as much as 45% recycled material which reduces our carbon footprint.
	Florim USA sources >95% raw material within a 500 mile radius, which results in a smaller carbon footprint.
G G REEN SQUARED	Tile Council of North America and the American National Standards Institute's standard for sustainability and environmental impact.
Environment PRIORITY ONE	A declaration that Florim USA values the environment and works daily to minimize our adverse impact upon it.
Чрс Version 2.0	The Health Product Declaration Collaborative transparency declaration for all of Florim USA's naturally occurring materials.
Certified Environmental Product Declaration www.nstorg	Certification of plant and product specific Environmental Product Declaration (EPD) which tracks environmental impacts from the production of porcelain tile.
CREEKCLARD CREEKCLARD Michael and Michael Creation	Underwriter's Laboratories certification of low emitting materials. Florim USA is Green Guard Gold certified.
Product Certification BUREAU VERITAS Certification	Bureau Veritas Standards Program verifies and certifies both pre- and post- consumer recycled content.
TILE COUNCIL OF NORTH AMERICA, INC.	Florim USA actively participates in the Tile Council of North America which allows us to be on the forefront of advances in the tile industry and its standards.
A REAL PROPERTY OF THE REAL PR	USGBC is committed to suit a more sustainable life. Florim USA supports this mission by manufacturing products which aid architects in achieving USGBC certification.
INTERNATIONAL LIVING FUTURE INSTITUTE	Florim USA's sustainability and social practices support the mission of The International Living Future Institute which strives to create a socially just, culturally rich, and ecologically restorative community.
	The Tennessee Recycling Coalition is dedicated to promoting recycling and sustainable material management practices, and awarded Florim USA the Tennessee Recycler of the Year award for 2020.

This product meets or exceeds all standards described in ANSI A137.1. Este product cumple o exceed todos los estandares de ANSI A137.1.

Progress that invests in the entire society

As an active member of the U.S Green Building Council, MILE[®] stone spreads awareness to the community and encourages the use of building solutions through environmentally friendly practices.

Our products positively contribute to the requirements for obtaining the LEED (Leadership in Energy and Environmental Design) and WELL (IWBI) certifications.


A commitment to environmental sustainability and responsibility

We are committed to conscious development that minimizes the negative impact of manufacturing production on the environment. Our general approach to sustainability intersects with our business strategy to embrace three areas of responsibility: economic, social, and environmental. Some ways we prove this are:

- Products containing as much as 45% recycled content.
- Post-consumer recycled content levels as much as 3%.
- · Zero industrial wastewater discharge.
- A 99% internal process recycling rate.
- Local sourcing of >95% raw materials (within 500-mile radius of factory) resulting in low transportation related carbon emissions.

MILE[®]*stone* is taking these and other steps, as well as actively investing to reduce carbon emissions to ensure that we reach full carbon neutrality.







300 International Blvd. Clarksville, TN 37040 | www.milestonetiles.com | 1-877-356-7461



8700987 v. 01/24