

PORCELAIN PAVERS





OUTDOOR 25 PORCELAIN PAVERS




BENEFITS +One Chalk Greige Ash Area 51 White Clay Steel Earth Moon White Miami White Manhattan Grey FARMHOUSE LIVING Alabaster Pewter Millstone imprint Intaglio Cool Intaglio Kaolin Intaglio Warm Lітн Legacy White Antique Cream Heirloom Blue Mood Wood White Honey Grey Quartz Extra White White Grey **Specifications**

INSTALLATION METHODS



		pg. 2
		pg. 7
		pg. 11
Black		
		pg. 15
Light Grey	Multicolor	Dark Grey
		pg. 23
15		
Slate		
		pg. 27
		pg. 31
		pg. 35
		ng 20
		pg. 39
		pg. 44
		pg. 46





Resistant to Thermal Shock Won't break due to gradual or sudden temperature changes (-40°F - 210°F).



Made from Natural **Raw Materials** Sourced locally within 500mi of our production facility, lowering our carbon footprint.



Unmatched Durability Stronger and more resilient than any alternative paving solution.



Frost Resistant Unaffected by frost or freezing since our pavers don't absorb water.



V.O.C. Free Emits 0 VOCs to protect occupants and environmental health.



Resists Microbial Growth and Damage

Unaffected by moss, mold, and verdigris.



Scratch and **Stain Resistant** Scratch and stain resistant, outdoor porcelain

pavers can handle high traffic areas.



Easy to Clean and Sanitize No harsh chemicals needed to clean, nonporous material is resistant to stains.



Versatile Installation **Applications** Install over grass or gravel, mortared in or simply laid on the ground.



UV Resistant and Colorfast

Won't fade from UV exposure, retains original color over product life.



Virtually No Maintenance

Once installed, pavers require minimal upkeep and are easy to replace.



Slip Resistant and Quick Draining Perfect for pool decks, terraces, or even simple garden paths.



Easy To Install Requires minimal materials and effort to install nearly anywhere.





Cost-Over-Life Savings

With a 60+ year life expectancy, our pavers provide a low life cycle cost analysis.





Available in a Broad **Range of Styles**

Styles range from stone, concrete, or wood looks in a variety of sizes.


✓ **QUARTZ** | GREY 24" x 24"





+ONE CONCRETE LOOK

SIZES



12" x 48" Rectified				
Chalk	1101411			
Greige	1101412			
Ash	1101413			

COLORS





GREIGE

◆ +ONE | GREIGE 12" x 48" + 24" x 24"

Colors shown may vary from actual product. Final selection should be made from actual product samples.




24" x 24" Rectified

Chalk	1101414
Greige	1101415
Ash	1101416











▲ +ONE | ASH 24" x 24"

★ +ONE | CHALK 12" x 48" + 24" x 24"



AREA 51 TERRAZZO LOOK

SIZES

24" x 48	8" Rectified	
White	1104834	
Clay	1104835	
Steel	1104836	
Black		

COLORS







BLACK

AREA 51 | STEEL 24" x 24"

Colors shown may vary from actual product. Final selection should be made from actual product samples.




24" x 24" Rectified

White	1104847
Clay	1104848
Steel	1104849
Black	1104850











▲ AREA 51 | CLAY 24" x 24"

▲ AREA 51 | BLACK 24" x 24"





SIZES



24" x 24" Rectified Dark Grey 1096343 Light Grey 1096344 Manhattan Grey 1096348 Miami White 1096349 Moon White 1096350 Multicolor 1096342

COLORS









✓ EARTH | MULTICOLOR 24" x 24"

Colors shown may vary from actual product. Final selection should be made from actual product samples.







▲ **EARTH** | MOON WHITE 24" x 24" + 12" x 24" COPING



► **EARTH** | MIAMI WHITE 24" x 24"

Tile removed to show raised installation on pedestals. For more information, see pg. 39.





▲ EARTH | DARK GREY 24" x 24"



FARMHOUSE LIVING 2 M STONE LOOK

SIZES

24" x 48" F	Rectified	
Alabaster	1104235	

1104235 1104236 Pewter Millstone 1104237 Slate 1104238

COLORS





MILLSTONE



✓ FARMHOUSE LIVING | ALABASTER 24" x 48"

Colors shown may vary from actual product. Final selection should be made from actual product samples.



24" x 24" Rectified


Alabaster	1104240
Pewter	1104241
Millstone	1104242
Slate	1104243








► FARMHOUSE LIVING | PEWTER 24" x 48"



► FARMHOUSE LIVING | MILLSTONE 24" x 48"



imprint

STONE LOOK

SIZES



 24" x 24" Rectified

 Intaglio Cool
 1105076

 Intaglio Kaolin
 1105077

 Intaglio Warm
 1105078

COLORS

INTAGLIO COOL INTAGLIO KAOLIN

✓ imprint | INTAGLIO KAOLIN + INTAGLIO WARM 24" x 24"


Colors shown may vary from actual product. Final selection should be made from actual product samples.





INTAGLIO WARM





▲ imprint | INTAGLIO COOL 24" x 24"

▲ imprint | INTAGLIO WARM 24" x 24"



LITH STONE LOOK

SIZES

24" x 48" Rectified Heirloom Blue 1103563 Antique Cream 1103562 Legacy White 1103561

Heirloom Blue Legacy White



1103576

12" x 12" Rectified Heirloom Blue Antique Cream

Legacy White

COLORS

Legacy White







LITH | HEIRLOOM BLUE 24" x 36" + 24" x 24" + 12" x 24" + 12" x 12"

Colors shown may vary from actual product. Final selection should be made from actual product samples.





1103581 1103580 1103579




Multisize Pattern Uses: 24" x 36", 24" x 24", 12" x 24", 12" x 12"











▲ LITH | LEGACY WHITE 24" x 24" + 24" x 48"



MOOD WOOD WOOD LOOK

SIZES



COLORS





✓ MOOD WOOD | WHITE 12" x 48"

Colors shown may vary from actual product. Final selection should be made from actual product samples.














▲ **MOOD WOOD** | HONEY 12" x 48"







SIZES

24" x 48" Rectified				
Extra White	1101846			
White	1101421			
Grev	1101422			

12" x 48" Rectified					
Extra White	1101847				
White	1101423				
Grey	1101424				

COLORS





WHITE

∢ QUARTZ | EXTRA WHITE 12" x 48"


Colors shown may vary from actual product. Final selection should be made from actual product samples.



24" x 24" Rectified

Extra White	1101848
White	1101426
Grey	1101427








▲ **QUARTZ** | WHITE 12" x 48" + 24" x 24"

▲ QUARTZ | GREY 24" x 24"


TRIM SPECIFICATIONS

COPING





Edge Details:

Radius: 10mm Diameter: 20mm




12" x 24" Coping with Stair Tread





12" x 24" L-Shaped Coping




12" x 24" Drain Coping with Stair Tread

Trim pieces and field tiles may come in different shades, the slab's edge may show layers of differing hues.

Outdoor coping trim pieces available through special order only. Contact your sales representative for more information.





TECHNICAL SPECIFICATIONS

This product meets or exceeds all standards described in ANSI A137.3. Este product cumple o exceed todos los estandares de ANSI A137.3.

	SPECS	TEST METHOD	INDUSTRY STANDARD	MILE®stone VALUES
5	D.C.O.F.	ANSI A326.3	≥ 0.42 WET	> 0.55 WET
*	FREEZE / THAW RESISTANCE	ASTM C1026	AS REPORTED	RESISTANT
~	CHEMICAL RESISTANCE	ASTM C650	AS REPORTED	NOT AFFECTED
×	STAIN RESISTANCE	ASTM C1378	AS REPORTED	NOT AFFECTED
	MAXIMUM STRAIGHTNESS DEVIATION % IN RELATION TO CORRESPONDING PRODUCT DIMENSIONS	ASTM C485	± 0.40% (± 1.3 mm)	± 10%
	THICKNESS VARIATION (THICKNESS RANGE WITHIN A MEASURED SAMPLE TESTED)	ASTM C499	± 1.5 mm (± 0.06 in)	± 0.5%
	LENGTH & WIDTH ADMITTED DEVIATION % OF AVERAGE SIZE OF EACH TILE FROM THE PRODUCTION DIMENSIONS	ASTM C499	± 0.5% (± 2 mm)	± 0.15%
	WATER ABSORPTION	ASTM C373	≤0.5%	≤0.5%
ڡ۠	BREAKING STRENGTH	ASTM C1505	≥ 2000 lbf AVERAGE (10.9 Kn)	≥ 2700 lbf INDIVIDUAL
*	RESISTANCE OF DEEP ABRASION	ASTM C1243	175 mm ³	< 150 mm ³
1	THERMAL SHOCK RESISTANCE	ASTM C484	PASS	MEETS REQUIREMENT

• Due to the inherent nature of fired porcelain tile, it is important to note that the coefficient of friction may vary within and between product runs.

CLEANING & MAINTENANCE / ROUTINE CARE INSTRUCTIONS



Scan the QR code with your smartphone.

PACKAGING SPECIFICATIONS

SIZES		THICKNESS (MM)	PIECES PER BOX	UOM PER BOX	WEIGHT PER BOX	BOXES PER PALLET	UOM PER PALLET	WEIGHT PER PALLET*
FIELD TILES								
12"x12" RECTIFIED	NOMINAL	20 mm	5	5 SF	45 LBS	45	225 SF	2,025 LBS
12"x24" RECTIFIED	NOMINAL	20 mm	4	8 SF	72 LBS	40	320 SF	2,880 LBS
12"x48" RECTIFIED	NOMINAL	20 mm	4	16 SF	147 LBS	16	256 SF	2,352 LBS
24"x24" RECTIFIED	NOMINAL	20 mm	2	8 SF	72 LBS	36	288 SF	2,592 LBS
24"x36" RECTIFIED	NOMINAL	20 mm	2	12 SF	108 LBS	16	192 SF	1,728 LBS
24"x48" RECTIFIED	NOMINAL	20 mm	2	16 SF	144 LBS	16	256 SF	2,304 LBS
QUARTZ 24"x48" RECTIFIED	NOMINAL	20 mm	2	15.5 SF	139.5 LBS	16	248 SF	2,232 LBS
COPING								
12"x24" COPING	NOMINAL	20 mm	4	8 SF	73.6 LBS	40	160 PCS	2,944 LBS
12"x24" STAIR TREAD COPING	NOMINAL	20 mm	4	8 SF	73.6 LBS	40	160 PCS	2,944 LBS
12"x24" DRAIN COPING	NOMINAL	20 mm	4	8 SF	73.6 LBS	40	160 PCS	2,944 LBS
12"x24" DRAIN COPING WITH STAIR TREAD	NOMINAL	20 mm	4	8 SF	73.6 LBS	40	160 PCS	2,944 LBS
12"x24" L-SHAPED COPING	NOMINAL	20 mm	4	8 SF	73.6 LBS	40	160 PSC	2,944 LBS

*WEIGHT PER PALLET DOES NOT INCLUDE PALLET WEIGHT ITSELF. All other sizes will be packaged as ordered. Please contact MILE®stone Customer Service at 1-877-356-7461 for packaging information. Minimum grout size recommended = 5 mm (or approx. 3/16") If staggered tile placement, we recommend using a 30% offset. If specified brick pattern with 1/2 pattern mandatory, a bigger grout is recommended to hide imperfections of installation (minimum 1/4").

INSTALLATION METHODS

DRY LAY ON GRASS OR SAND



DIY Video

MATERIALS:

- Outdoor 2cm Porcelain Pavers
- Paving Sand (optional)

Direct lay installations are the easiest, fastest, and most DIY-friendly way to lay your porcelain pavers. Perfect for garden pathways or a makeshift patio, consider digging out 2" of soil and pouring road base into the hole before laying the pavers to ensure a more stable and quick-draining walkway.

ADHESIVE INSTALLATION



DIY Video

DRY LAY ON GRAVEL

DRY LAY ON RAISED PEDESTALS



DIY Video

MATERIALS:

- Outdoor 2cm Porcelain Pavers
- Road-base Gravel

Perfect for patios and other outdoor large seating areas, installing over gravel allows for a more permanent and solid foundation for your pavers, while maintaining the ease and simplicity of DIY installation.



DIY Video

MATERIALS:

- Outdoor 2cm Porcelain Pavers
- Concrete Base
- Cement Based Adhesive
- Outdoor Grout

Have an old stained and worn down concrete slab patio you're looking to refresh? Look no further, as our porcelain pavers can be installed over a concrete base, revitalizing your existing outdoor foundations.

MATERIALS:

- Outdoor 2cm Porcelain Pavers
- Level Concrete Base
- Support Pedestals

Most suitable for commercial applications, installing on raised pedestals allows for excellent drainage. Also hides unsightly wiring, piping, or duct work, while keeping it all easily accessible.

GREEN MEMBERSHIPS & ACCREDITATIONS

	DESCRIPTION
Red List Free Declare.	Declare labels disclose all intentionally added ingredients and residuals present in the final product. Being Red List Free means the worst materials, chemicals, and elements for human and environmental health are not present within our products.
HpJ VERSION 2.0	The Health Product Declaration Collaborative transparency declaration for all of Florim USA's naturally occurring materials.
THE INTERNATIONAL EPD* SYSTEM	Certification of plant and product specific Environmental Product Declaration (EPD) which tracks environmental impacts from the production of porcelain tile.
G G REEN SQUARED	Tile Council of North America and the American National Standards Institute's standard for sustainability and environmental impact.
CREEVCUADD CREEVCUADD In the status in the status in the status in the status in the status in the status	Underwriter's Laboratories certification of low emitting materials. Florim USA is Green Guard Gold certified.
Recycled Contract	Defines post-consumer content of as much as 3% recycled material which reduces landfill impact. Certified by Bureau Veritas.
Recipied Contract	Defines pre-consumer content of as much as 45% recycled material which reduces our carbon footprint. Certified by Bureau Veritas.
INTERNATIONAL LIVING FUTURE INSTITUTE	Florim USA's sustainability and social practices support the mission of The International Living Future Institute which strives to create a socially just, culturally rich, and ecologically restorative community.
MENTER EN	USGBC is committed to suit a more sustainable life. Florim USA supports this mission by manufacturing products which aid architects in achieving USGBC certification.
	Florim USA sources >95% raw material within a 500 mile radius, which results in a smaller carbon footprint.
TICK OF NORTH AMERICA. INC.	Florim USA actively participates in the Tile Council of North America which allows us to be on the forefront of advances in the tile industry and its standards.
	The Tennessee Recycling Coalition is dedicated to promoting recycling and sustainable material management practices, and awarded Florim USA the Tennessee Recycler of the Year award for 2020.
EO 9001 Daty Sparse Convector	ISO 9001 & ISO 14001 are globally recognized standards. ISO 9001 certifies that Florim USA products and practices continually meet and exceed customer and regulatory requirements. ISO 14001 certifies that Florim USA complies with environmental regulations and that it's manufacturing practices are environmentally conscious.
BENEFIT	Florim USA updated its corporate charter in 2022 to become a Benefit Corporation. Our company is committed to maintaining this designation through initiatives focused on sustainability, social responsibility, ethical business practices and transparent, annual reporting on our social and environmental performance.

Progress that invests in the entire society

As an active member of the U.S. Green Building Council, MILE®stone spreads awareness to the community and encourages the use of building solutions through environmentally friendly practices. Our products positively contribute to the requirements for obtaining the LEED (Leadership in Energy and Environmental Design) and WELL (IWBI) certifications.

A commitment to environmental sustainability and responsibility

We are committed to conscious development that minimizes the negative impact of manufacturing production on the environment. Our general approach to sustainability intersects with our business strategy to embrace three areas of responsibility: economic, social, and environmental. Some ways we prove this are:

- Products containing as much as 45% recycled content.
- Post-consumer recycled content levels as much as 3%.
- · Zero industrial wastewater discharge.
- A 99% internal process recycling rate.
- Local sourcing of >95% raw materials (within 500-mile radius of factory) resulting in low transportation related carbon emissions.

MILE[®] stone is taking these and other steps, as well as actively investing to reduce carbon emissions to ensure that we reach full carbon neutrality.









300 International Blvd. Clarksville, TN 37040 | www.milestonetiles.com | 1-877-356-7461

